

KEITOKU specification reference

Issued : Dec. 20 '01

Base model name : **PL25,60,81,82**

KEITOKU model name

PL - L
└─┬─┘ └─┬─┘ **Cable length**
 └─┘ └─┘ **Series name (25, 60, 81, 82)**

Cable length

AB = 0.2m AC = 0.3m AD = 0.4m AF = 0.6m AG = 0.7m AH = 0.8m
AJ = 0.9m AK = 0.25m
01 = 1m 02 = 2m 04 = 4m 06 = 6m 08 = 8m 09 = 9m 11 = 11m
12 = 12m 13 = 13m 14 = 14m
0A = 0.5m 0B = 1.5m 0C = 2.5m 0D = 3.5m 0E = 4.5m 0F = 5.5m
0G = 6.5m 0H = 7.5m 0I = Not in use 0J = 8.5m 0K = 9.5m 1A = 10.5m
1B = 11.5m 1C = 12.5m 1D = 13.5m 1E = 14.5m

KEITOKU specification list

Issued : Dec. 20 '01

Base model name : **PL25,60,81,82**

Entry items		KEITOKU range
Cable length	L = ()m	<ul style="list-style-type: none">- PL25, PL60 ...It is available only without cable armor. From 0.2m to 0.9m by 0.1m pitch From 1.0m to 10m by 0.5m pitch- PL81, PL82 ...It is available only without cable armor. From 0.5m to 14.5m by 0.5m pitch- Tolerance is general tolerance. <p>Note) With cable armor is dealt with as TOKUREN model.</p>